

## Fuller® 5- & 6-Speed Transmissions

FS-6305A  
FS-6305B

FS-5406A  
FS-6406A

FSO-6406A  
FSO-8406A

# Eaton's "Robust Transmission System" Provides the Best Value in the Medium-Duty Market!

The Robust Transmission System combines an industry-preferred Fuller® Transmission with a Solo® Self-Adjusting Clutch to deliver:

- **Up to 60 – 70 Percent Lower Life Cycle Cost than a conventional automatic!**
  - No clutch adjustments – **Up to \$1,800\* in potential cost savings!**
  - Longer wearing synchronizer material reduces synchronizer replacements — Up to \$1,300\* in potential cost savings!
- **Increased Uptime and Improved Productivity**
  - No clutch adjustments, more durable synchronizers and improved seals means less required maintenance...resulting in increased vehicle uptime and improved productivity.
- **Extended Protection Plans Available –**

Now, you can purchase the extended warranty coverage you expect from Eaton. Please refer to Eaton's Vocational Warranty Guidelines, item number TCWY0900, contact a Roadranger at 800-826-HELP (4357) or visit our website at [www.eaton.com/roadranger](http://www.eaton.com/roadranger) for specific details about the Extended Protection Plan coverage options, current pricing and vocations that qualify.

\*Savings are based on 6 years/200,000 miles of service. Your results may vary.

### The New Robust Package Delivers Increased Uptime, Extended Life and Lower Life Cycle Cost\*

Eaton  
5- & 6-Speed  
w/Solo Clutch

Up to 60–70% Lower Life Cycle Cost

Torque  
Converted  
Automatic

\* Life Cycle Cost based on 200,000 miles/6 years.

# EATON

Powering Business Worldwide

BACKED BY

## Roadranger


SUPPORT

# Fuller® 5- & 6-Speed Transmissions

Speeds	Model	Lbs.-Ft. Max TQ	Overall	Rev.	1	%	2	%	3	%	4	%	5	%	6	Oil Cap. Pints [ltr]	Length* Inches [mm]	Weight** Lbs. [kg]	PTO Speed (% of Engine)
5 forward, 1 rev.	FS-6305A	660 [895 Nm]	7.22	7.22	7.22	86	3.89	75	2.22	60	1.39	39	1			19.5 [9]	25.6 [650]	369 [167]	46
	FS-6305B	660 [895 Nm]	7.22	7.22	7.22	86	3.89	75	2.22	75	1.27	27	1			19.5 [9]	25.6 [650]	369 [167]	46
6 forward, 1 rev.	FS-5406A	560 [759 Nm]	9.01	8.63	9.01	71	5.27	64	3.22	58	2.04	50	1.36	36	1	19.5 [9]	25.6 [650]	359 [163]	52
	FS-6406A	660 [895 Nm]	9.01	8.63	9.01	71	5.27	64	3.22	58	2.04	50	1.36	36	1	19.5 [9]	25.6 [650]	359 [163]	52
	FSO-6406A	660 [895 Nm]	9.04	6.75	7.05	71	4.13	64	2.52	58	1.59	29	1	28	0.78	19.5 [9]	25.6 [650]	359 [163]	68
	FSO-8406A	860 [1166 Nm]	9.04	6.75	7.05	71	4.13	64	2.52	58	1.59	59	1	28	0.78	19.5 [9]	25.6 [650]	359 [163]	68

\* With SAE #2 aluminum clutch housing, standard controls, less clutch release components and shift tower. Dry weight.

\*\* Lengths listed are from face of clutch housing to front bottoming surface of companion flange or yoke. SAE #2 (6.625" [168.3 mm] depth.)



## Specifications:


PTO Openings:

- Both left and right, 6-bolt PTO


PTO Drive Gears:

- FS-6305A: 39-tooth, 6.4 pitch, 22° R. H. Helix
- FS-6305B: 41-tooth, 6.5 pitch, 23° R. H. Helix
- FS-5406A & FS-6406A: Left and right sides operate off 5th speed countershaft gear. 38-tooth gear, 6.35 pitch, 22° Helix Angle, 20° Pressure Angle
- FSO-6406A & FSO-8406A: Left and right sides operate off the overdrive countershaft gear. 48-tooth gear, 7.00 pitch, 26° Helix Angle, 23° Pressure Angle

## 5-Speed Shift Pattern



## 6-Speed Shift Pattern



BACKED BY

**Roadranger**

SUPPORT

For spec'ing or service assistance, call 1-800-826-HELP (4357) or visit [www.eaton.com/roadranger](http://www.eaton.com/roadranger). In Mexico, call 001-800-826-4357.

Roadranger: Eaton and trusted partners providing the best products and services in the industry, ensuring more time on the road.

Eaton

Vehicle Group  
P.O. Box 4013  
Kalamazoo, MI 49003 USA  
800-826-HELP (4357)  
[www.eaton.com/roadranger](http://www.eaton.com/roadranger)

© 2013 Eaton  
All Rights Reserved. Printed in USA.  
TRSL0191 0713

**Note:** Features and specifications listed in this document are subject to change without notice and represent the maximum capabilities of the software and products with all options installed. Although every attempt has been made to ensure the accuracy of information contained within, Eaton makes no representation about the completeness, correctness or accuracy and assumes no responsibility for any errors or omissions. Features and functionality may vary depending on selected options.